



” Fanless 17” All-in-One POS System

Specifications - P3100

- **Elegant POS system for demanding users**
- **Perfectly protected against liquids thanks to robust IP64 front pane**
- **No fan: quiet and reliable**
- **Direct power supply for peripherals via 24 V PoweredUSB**

		P3100
System	CPU	Intel Celeron J1900 QC 2.0 Ghz
	System memory	4 GB SO-DIMM, DDR3L, 1333 MHz, max. 8 GB (1 bank)
	Chipset	Intel Baytrail platform
	Hard disk drive	Min. 320 GB HDD, optional SSD
	Graphics chip	Intel HD graphics
	Supported operating systems	WS7E, POSReady 7, Windows Embedded 8.1 Industry, Linux
	Housing	Aluminium
Display	LCD screen size	43.2 cm (17") LCD
	Maximum resolution	1280 x 1024 pixels
	Brightness	250 nits, LED
	Touch screen	5-wire resistive, PCAP
Interfaces	USB	3x 2.0, 1x 3.0, 1x 24V pUSB
	eSATA	1x
	Serial/COM	3x DB9, 1x RJ45 (powered)
	Parallel	Optional
	LAN	1x Gigabit
	VGA	1x
	Cash drawer port	1x (12 V RJ11)
PSU	Power adapter	150 watts (integrated in the stand)
Other	Dimensions (WxDxH)	410 x 385 x 296 mm (with stand)
	Operating temperature	0 to 35 °C
	Certification	CE, FCC, RoHS
	Mount	VESA 100 x 100 mm
Options	Customer display	2 x 20 characters (integrated)
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") pole
	Barcode scanner	1D or 2D barcode scanner
	Waiter lock	iButton, Addimat
	RFID	MIFare
	Colour	Black
	UPS	Optional

Your partner