



” Fanless 17" All-in-One POS System

Specifications – P3100

- **Elegant POS system for demanding users**
- **Perfectly protected against liquids thanks to robust IP64 front pane**
- **No fan: quiet and reliable**
- **Direct power supply for peripherals via 24 V PoweredUSB**

		P3100
System	CPU	Intel Celeron J1900 QC 2.0 Ghz
	System memory	4 GB SO-DIMM, DDR3L, 1333 MHz, max. 8 GB (1 bank)
	Chipset	Intel Baytrail platform
	Hard disk drive	128 GB SSD, optional HDD
	Graphics chip	Intel HD graphics
	Supported operating systems	WS7E, POSReady 7, Windows Embedded 8.1 Industry, Linux / Windows 10
	Housing	Aluminium
Display	LCD screen size	43.2 cm (17") LCD
	Maximum resolution	1280 × 1024 pixels
	Brightness	250 nits, LED
	Touch screen	5-wire resistive, PCAP
	Tilt angle	0 to 90°
Interfaces	USB	3× 2.0, 1× 3.0, 1× 24 V pUSB
	eSATA	1×
	Serial/COM	3× DB9, 1× RJ45 (powered 5 V / 12 V available)
	Parallel	Optional
	LAN	1× Gigabit
	VGA	1×
	Cash drawer port	1× (12 V RJ11)
PSU	Power adapter	150 watts (integrated in the stand)
Other	Dimensions (WxDxH)	410 × 385 × 296 mm (with stand)
	Operating temperature	0 to 35 °C
	Certification	CE, FCC, RoHS
	Mount	VESA 100 × 100 mm
Options	Customer display	2 × 20 characters (integrated)
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") pole
	Barcode scanner	1D or 2D barcode scanner
	Waiter lock	iButton, Addimat
	RFID	MIFare
	Colour	Black
	UPS	Optional

Your partner